FI180





5 0 0





HUMAN CARE SWEDEN (HQ) Årstaängsvägen 21B 117 43 Stockholm

117 43 Štockholm Phone:- +46 8 665 35 00 Fax:- +46 8 665 35 10 info.se@humancaregroup.com Our FL180 floor lift is a stable and flexible floor lift that can be used in all types of lifting situations. It allows for lifting from high surfaces, such as a chair, bed, wheelchair or commode, in addition to lifting from the floor. The FL180 is the perfect solution as a complement to our overhead lift for several lifting situations.

Flexible

The FL180 easily lifts from both low and high surfaces to move a patient from a bed, seated position or even the floor. It works seamlessly with most of our loop slings, allowing it to be used in many different lifting situations. The low floor height ensures it easily fits under most furniture and its portability allows it to easily be moved between different rooms or departments in facilities. It is an optimal solution when overhead lift installations are not possible or planned or for use in corridors. It also offers a versatile temporary solution when a lift is required only for a short period of time or when waiting for a permanent solution.

Easy to Use

The FL180 features LINAK actuators and easy

HUMAN CARE CANADA

10-155 Colonnade Road Ottawa, ON K2E 7K1 Phone: +613.723.6734 Fax: +613.723.1058 info.ca@humancaregroup.com

HUMAN CARE NEDERLAND

Elspeterweg 124 8076 PA Vierhouten Phone: +31 577 412 171 Fax: +31 577 412 170 info.nl@humancaregroup.com

to maneuver wheels, two of which feature a braking system for security when loading or unloading a patient. Its base can be adjusted electronically and it features manual or electric emergency lowering. The display panel clearly indicates battery levels and service requirements.

Quality

Our products are designed and manufactured to meet all the requirements of relevant ISO, UL, IEC and EN standards. At every stage of the development process, every single product is given extensive attention in design, developement and manufacturing. This means that a user of this product feels confident with its reliability and the caregiver feels confident with its safety.

> HUMAN CARE UNITED STATES 8006 Cameron Road, Suite K

8006 Cameron Road, Suite K Austin, TX 78754 Phone: +512.476.7199 Fax: +512.476.7190 info.us@humancaregroup.com

Accessories







Upholstered Cover Protects user from injury. Not for use in wet environments. Does not work with small (70979). Part no. 50866



Slings Assorted sizes and models of Human Care slings can be used with this product.



Hand Control Included with floor lift. Lift arm up/down, leg mast open/closed functions. Replacement Part no. 70974

Technical Specifications

FL180 Floor Lift			
Part No.	70967-[Country Code]	Lifting Interval	132cm / 52"
Width	63cm / 24.8"	Turning Radius	120cm / 47.2"
Length	114cm / 44.9"	Wheels	$\ensuremath{\text{?.5cm}}\xspace/3$ " (twin wheels), rear with footoperated brake
Height	Arm Lowered: 145cm / 57.1" Arm Raised ¹ : 199cm / 78.3"	Battery	Lead-acid, 2.9Ah 24V Replacement Part no. 70975
Height from Floor	11.5cm/4.5"	Hanger Bars	Small 37cm/14.6" Part no. 70977
Adjustable Leg (Min - Max)	Inside: 52cm - 99cm / 20.5" - 39" Outside: 63cm - 111cm / 24.8" - 43.7"		Medium 47cm/18.5" Part no. 70978
Weight	32kg/70.5lb		Large 50cm/19.7" Part no. 70979
Weight Capacity	180kg/397lb	Power Cable	Replacement Part no. 70980 (EU), 70981 (UK), 70982 (US), 70983 (AU)
IP Rating	IPX4		

¹Measurement based on arm mast at highest setting

Lifting Situations



Use to/from a chair Use to raise/lower a

Use to/from a bed

Use to raise/lower a

patient from/to a bed.



Use to/from the floor Use to raise/lower a patient from the floor.



Use to/from the toilet Use to raise/lower a patient from/to a toilet.

Features



Indicates low battery level and service requirement.



Emergency Lowering Manual or electric.

emergency situations.

Reset by turning counter



Tested to all relevent standards, including ISO 10535, hoists for the transfer of disabled persons.

Emergency Stop Cuts power to lift for

clockwise.

LED indicator



